

8160WB DC BATTERY BACKUP CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Trusted reliability with battery backup.



RELIABLE

INTEGRATED BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

DC MOTOR IS PURPOSEFULLY DESIGNED FOR QUIET PERFORMANCE.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

SOFT START/STOP FOR SMOOTH OPERATION.

WARRANTY 4-YEAR MOTOR, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

SECURE

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY myQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®
Includes lockout controls and accessory programmability.



882LMW

3-BUTTON REMOTE CONTROL
Operates up to 3 openers or myQ Light Accessories.



893LM

INTEGRATED BATTERY BACKUP
Powers up the opener when the power's out.



485LM

POWERFUL ADD-ONS:

myQ HOME BRIDGE
Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.***



819LMB

MINI UNIVERSAL REMOTE CONTROL
Compact and portable to provide quick, easy garage access.



374UT

REMOTE LIGHT CONTROL
Plug in any lamp to this device to control it with a smartphone or garage remote.



825LM

GARAGE DOOR AND GATE MONITOR
Monitors and closes up to 4 garage doors from any room in the house.



829LM

The State of California has not endorsed these or any other garage door openers. *Requires additional purchase of myQ Home Bridge 819LMB. **Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. ***Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV® with tvOS™ 10.0 or later or an iPad® with iOS 10.0 or later set up as a home hub. Smartphone not included. Application screens may vary. Cellular data or Wi-Fi connection required. Test equipment regularly and follow safety instructions.

PRODUCT GUIDE 8160WB
DC BATTERY BACKUP CHAIN DRIVE
WI-FI GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWF)



DIMENSIONS

| Rail Options | 7' | 8' | 10' |
|------------------|------|------|-------|
| Installed Length | 128" | 140" | 164" |
| Max. Opening | 7'6" | 8'6" | 10'6" |

Headroom Clearance Required: 2"

8.5"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: **~200'**

Operating Temperature: -30°F to 150°F
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only.
Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

myQ® RADIO



- Provides 2-way communication from garage door opener and myQ accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER**)

**May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 1 100-Watt Lightbulb
- Adjustable-Time Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

SHIPPING.

SHIPPING WEIGHT (in lbs.)



HEAD



RAIL (7')

CARTONS (2)

CARTON 1: 19.81" x 11.94" x 11.19"

- Garage Door Opener Head (8160WB)
- Battery (485LM)

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Integrated Battery Backup
- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 myQ Devices



***WARNING:** to reduce the risk of injury to persons—
ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.

© 2019 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc. 300 Windsor Drive, Oak Brook, IL 60523
LiftMaster.com

ALARM.COM is a registered service mark of Alarm.com. Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc. Google, Google Home, Google Assistant and other related marks and logos are trademarks of Google Inc. Nest is a trademark of Nest Labs, Inc. XFINITY Home and the XFINITY Home design logo are trademarks or service marks of Comcast Corporation. UL® and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation.
LMGDENPG8160WB 2/19

LiftMaster®