



FREE EXIT BOX

Rugged box for simple keyless exit



FEB100-NT



FEB100-PB



FEB100-TP

FEB100 Series

- No Touch, Push Button or Touch Plate Design
- Built-in Time Delay For Pedestrian Doors
- Rugged Housing With Built-in LED Light

The FEB100 Free Exit Box series offers simple exit control through automatic gates and pedestrian doors. It uses a no touch sensor, metal push button or metal touch plate and is housed in a rugged steel housing. The built-in time delay is ideal for applications when the Free Exit Box is placed back from the pedestrian door. And the LED light makes the FEB100 easy to use day or night.





The Free Exit Box offers simple exit control through automatic gates and pedestrian doors. It uses a metal touch plate with no moving parts and is housed in a rugged steel housing.

Free Exit Box

Rugged Outdoor Touch Plate Box

Features:

- FEB100-NT: No Touch IR sensor with manual override
- FEB100-PB: Metal push button with LED halo light
- FEB100-TP: Simple to use touch plate with no moving parts
- Lighted, recessed design for easy nighttime use.
- LED housing light offers low power consumption lighting.
- Built-in relay time delay is ideal for pedestrian doors and walk gates.
- Single relay offers NO, NC and C output for use with gate operators, electric strikes, and magnetic locks.
- Stainless steel hinged door.
- Built-in lock for easy service access.
- Brushed aluminum faceplate for clean look.
- UV Protected powder coat paint.
- Rugged weather tight, vandal resistant design.
- Locked and hinged faceplate for easy service access.
- 12-24 VAC or VDC to work with a wide range of transformers, gate operators, and other power sources.

Specification	FEB100-NT	FEB100-PB	FEB100-TP
Sensor design	No touch IR	Metal push button	Touch plate
Buzzer	None	None	Internal
Power LED	Red Halo LED	Green Halo LED	Red
Activation LED	Green	None	Green
Time delay adjustment	1-30 seconds	1-90 seconds	1-99 seconds
Relay functions	Momentary, Latch	Momentary, Latch	Momentary
Number of relays	1	1	1
Relay outputs	NO, NC, C	NO, NC, C	NO, NC, C
Housing light	White LED	White LED	White LED
Hinge	Stainless steel	Stainless steel	Stainless steel
Conduit hole - Back	3/4" centered	3/4" centered	3/4" centered
Mounting holes	3" x 3" centered	3" x 3" centered	3" x 3" centered
Power Input	12-24 VDC	12-24 VAC/VDC	12-24 VAC/VDC
Pushbutton Halo power	12-24 VDC	12 VDC	None
Dimensions	6"H x 4"D x 3.5"D	6"H x 4"W x 3.5"D	6"H x 4"W x 3.5"D



FEB100-NT



FEB100-PB



FEB100-TP



DO NOT mount operating devices accessible through the gate or in between gate and wall.

Mount the system at least 10 feet away from a vehicular gate and its travel.

Revision D