

POWER YOUR BUSINESS

with LiftMaster® Central Motors

Superior Performance Durability and Security

Our line of Central Motors provides the highest level of performance for rolling door applications. All LiftMaster® Central Motors come standard with a Key Lock Box to enable more secure, controlled access to the door.



LM-1600
Single Electric Motor



INCLUDED:

Key Lock Box (CM-LB120)

Standard with both motors, this Key Lock Box provides controlled access to a water-resistant constant Pressure-To-Close switch and manual brake release lever.

STANDARD FEATURES

Model Number	LM-1600	LM-2000
Power Supply Voltage (+/-10%)	120VAC (LM-1600)	120VAC (LM-2000)
Power Draw	5.0 A/590 W (LM-1600)	5.5 A/635 W (LM-2000)
Motors (Electric)	Single	Single
Drive Torque	150 Nm	180 Nm
Maximum Lifting Capacity	160 kg/362 lbs.	200 kg/440 lbs.
Winding Flange Speed	12 RPM	12 RPM
Shutter Shaft Diameter	60 mm (48 mm)	60 mm (48 mm)
Flange/Drum Diameter	200 mm/220 mm	200 mm/220 mm
Operator Weight	9 kg/19.9 lbs.	10.5 kg/23.2 lbs.
Manual Limits	Electro-Mechanical	Electro-Mechanical
Brake Type	Electric	Electric
Door Release	Manual	Manual
Overload Protection	4 min. w/Reset	4 min. w/Reset
Regulatory Requirements	IEC UL 325 (Model LM-1600 only)	IEC UL 325 (Model LM-2000 only)
Warranty (Limited)	2-Year Limited	2-Year Limited

Place your order today or for more information contact:
Paul Golevicz • Senior Product Manager • 630.516.5340

LiftMaster®