

Suprex SPX-7400 Series

Features:

- Available in single mode or multi-mode
- Includes complete solution with remote (reader/gate/door) and central (panel) interface.
- Service mode for setup and configuration of Expansion modules.
- Field configurable reader formats
- Multifunction indicator for determining operational status of the unit
- Auxiliary I/O connections available for Door/Gate/Panel status signaling.
- Multiplexing of RF bridge providing for additional door/gate on a single RF link.
- Economical expansion capabilities using Suprex Lynk technology

Fiber Optic Specifications:

Module connections utilize standard "ST" style connections

NOTE: Single Mode or Multi Mode must be Specified at time of order, Default configuration is MultiMode

SPX-7400 Multimode:	Loss Budget	13 dB	850 nm	62.5/125 Fiber
	Loss Budget	9 dB	850 nm	50.0/125 Fiber

SPX-7410 Single mode:	Loss Budget	20 dB	1300 nm	9/125 Fiber
-----------------------	-------------	-------	---------	-------------

Electrical and Mechanical Specifications

Physical	SPX-7400 - Aluminum Enclosure 4.45" x 3.08" x 2.0" (Each Unit)	
Temp	Storage(-55°C to + 150°C) Operating(-40°C to +80°C)	
Humidity	95% (non-condensing)	
Power	Input	Unreg Input 8 to 16 VDC* @ 300mA Max
	Output	+5VDC @100mA
Data I/O	Interface	Reader -Wiegand, Strobed (Clock & Data), F/2F LED - 0 - 30V
Relays	Max Switching	(220Vdc 30W (resistive) 1A)
		(250Vac 37.5VA 1A)
	Running Spec with load	(30Vdc 1A (resistive), 1 x 10 ⁵ operations at 20° C
		125Vac .3A (resistive), 1 x 10 ⁵ operations at 20° C

Cypress Computer Systems Inc. Lapeer, MI 48446 www.cypressworld.com @2011